

BIOFA Floor Soap, gray Article No. 2095

Properties

BIOFA Floor Soap gray is a premium, highly-concentrated soap combination from natural raw materials for cleaning, maintaining, and enhancing soaped, bleached, and oiled finishes. It gives the treated wood finishes a grayish appearance. With high solids content, phosphate and sulphate-free. For normal use softwood floors such as in residential and sleeping areas, for wall and ceiling paneling, and for furniture and doors.

Ingredients

Water, 5-15% alkaline-saponified coconut and soy oil fatty acid, titanium oxide, iron oxide, lavanden oil (contains linalool).

Application

Initial base coat only for soaped and for bleached surfaces:

Mix 1 part floor soap with 7 parts of hot water. Apply liberally and allow to soak for approx. 20 minutes. Then blend in with brush or buffing fleece. Collect and remove excess soap with rubber squeegee. Repeat procedure 2-3 times after 3 hours of drying time each. Polishing out with a white pad after each drying generates a particularly beautiful finish.

For cleaning and maintaining soaped, bleached, and oiled substrates:

Mix 1 part of floor soap with 40 parts of hot water. Wipe the floor to a damp film. Scrub as needed or treat with a buffing fleece. A short soaking time increases cleaning effectiveness. A finish maintained in this manner becomes increasingly less sensitive after each application. Repeat procedure 2-3 times as needed.

For cleaning and maintaining oil substrates:

Mix 1 part of floor soap with 40 parts of hot water. Only wipe the floor to a damp film and allow to dry. Do not use micro-fibers!

Carefully loosen heavy and tough dirt buildup with a white pad and a little soap solution.

Then wipe off with clean soap solution and allow to dry.

Do not wipe off with clear water!

Attention! Store diluted soap in a cool place and use within 14 days. Stains or yellowish discolorations may otherwise form on the wood.

Equipment cleaning

Clean with water immediately after use.

Yield per coat

10-15 m²/l undiluted wood floor soap.

At a mixing ratio of 1:7, 1 liter of undiluted wood floor soap is enough for 70-100 m².

At a mixing ration of 1:40, 1 liter of undiluted wood floor soap is enough for 400-600 m².

Storage

Keep cool, dry and properly sealed.

Keep away from frost.

Container

1 l / 5 l PE or PP containers

Hazard warnings



Attention
Causes serious eye irritation.

The information and instructions in the technical leaflet are binding. Prior consultation with the application engineering department of BIOFA is required if a deviation from these specifications is necessary. The generally accepted construction engineering practices must be observed. All previous information is null and void after the publication of this leaflet.

Safety instructions

Keep away from children. Read label before use. Clean hands thoroughly after using product. Wear safety gloves / safety gear / safety goggles / facial mask. WHEN INGESTED: Immediately call POISON INFORMATION CENTER or get medical help. ON EYE CONTACT: Gently rinse with water for several minutes. Remove contact lenses when possible. Continue rinsing. If eye irritation persists: Get medical advice/medical help.

Disposal

Use up product completely whenever possible. Dispose liquid product leftovers and partially full and cleaned containers in compliance with local statutory regulations. Only recycle fully emptied and cleaned containers.

German Waste Classification Directive [Abfallverzeichnis Verordnung - AVV] waste code 1aw. European waste classification: 20 01 29*

The information and instructions in the technical leaflet are binding. Prior consultation with the application engineering department of BIOFA is required if a deviation from these specifications is necessary. The generally accepted construction engineering practices must be observed. All previous information is null and void after the publication of this leaflet.